

Remcon's GUARDSAFE 42 barrier is a water-filled Longitudinal Channelizing Device (LCD) ideal for traffic and pedestrian channelization in almost any environment. The barricade is manufactured with rotationally-molded polyethylene, which allows it to withstand the harshest weather conditions and resist dents and cracks.

• Each unit includes:

- •Tongue and groove end feature, which allow connected units to form continuous lines and curves angled up to 15 degrees.
- •Features two molded-in pockets which easily accept standard blinking lights.
- Molded-in recessed handles, two forklift holes, and its lightweight design make transportation and positioning easier for users.
- Available in three standard weights and three standard high-visibility colors: natural, orange, and yellow. Custom colors available upon request.
- Ideal for temporary work zones, checkpoints, security, as well as crowd and traffic control.
- •Can be used as a TL-2 Barrier when used with steel pipe couplers.



## GUARDSAFE® 42 BARRIER



**GS42** 

Product Description	Width		Length		Height		Weight	
	in	cm	in	cm	in	cm	lbs	kgs
GUARDSAFE® 42 Lightweight	24	60.96	72	182.88	42	106.68	100	45.35
GUARDSAFE® 42 Standard	24	60.96	72	182.88	42	106.68	130	58.96
GUARDSAFE <sup>®</sup> 42 Heavyweight	24	60.96	72	182.88	42	106.68	170	77.11

Inches of Water	U.S. LBS	U.S. Gallons	<b>Cubic Feet</b>
40	1655	182.9	24.5
32	1410	153.5	20.5
24	1165	124.1	16.6
16	875	89.3	11.9
8	500	44.4	5.9
0	130	-	-

